





503cc. EFI Engine



New front LED light



All new 12" rims



Handlebar mounted switch for selecting 4x2 - 4x4 and front differential interlock



New rear LED light



Adjustable dual rear shocks

## **525i SE IRS 4x4**

### The ultimate in pleasure



ENGINE

- Engine Type 503 cc,

- Ignition

- Starter - Bore×Stroke

- Compression Ratio - EFI System

- Max Power

- Max Torque 46.1 Nm / 5500 rpm EC:31.0 Nm / 3500 rpm

**ECU** 

10.2

Electric

Ø 92 × 75.6 mm

28.9 kw / 6500

38 mm Throttle Body

Single Cylindrer, SOHC

DRIVETRAIN

4x4 Shaft Drive - Drive System L/H/N/R - Gear Selection - Transmission V-belt CVT Automatic

CHASSIS

- Front Suspension Double A-Arm - Rear Suspension Double A-Arm - Front Brakes Disc

- Rear Brakes - Front Tires

AT25 × 8-12 AT25 × 10-12 - Rear Tires

### DIMENSIONS/CAPACITIES

- Wheelbase - Length/Width/Height

- Seat Height 920 mm 18 L - Fuel Capacity - Ground Clearance 305 mm

- Base Weight OTHER

- Electrical Outlet Connector DC 12V 10A 120W



1280 mm

2155/1118/1235 mm

















WHITE











digital instrumentation



New front LED light



3000 / Ibs winch with handlebar control





switch for selecting 4x2 - 4x4 and front differential interlock



Parking gear lock



Passenger backrest &



New rear LED light

Adjustable dual



# **550i LT IRS 4x4**

- Base Weight

OTHER



### **ENGINE**

- Engine Type	503 cc
	Single Cylindrer, SOHC
- Ignition	ECU

- Starter Electric - Bore×Stroke Ø 92 × 75.6 mm

- Compression Ratio 10.2 - EFI System/ 38 mm Throttle Body Carburetor Peogrammed Fuel Injection - Max Power 28.9 kw / 6500 rpm

EC:14.5 kw / 5500 rpm 46.1 Nm / 5500 rpm - Max Torque EC:31.0 Nm / 3500 rpm

#### DRIVETRAIN

4x4 Shaft Drive - Drive System - Gear Selection L/H/N/R/P

- Transmission V-belt CVT Automatic CHASSIS

- Front Suspension Double A-Arm - Rear Suspension Double A-Arm - Front Brakes Disc

- Rear Brakes Disc - Front Tires AT26 × 8-14 - Rear Tires AT26 × 10-14

COLORS

### DIMENSIONS/CAPACITIES

- Wheelbase	1450 mm
<ul> <li>Length/Width/Height</li> </ul>	2360/1235/1250 mr
- Seat Height	940 mm
- Fuel Capacity	18 L
- Ground Clearance	335 mm

- Electrical Outlet Connector DC 12V 10A 120W



364 kg



Disc brakes with ø 230 mm



Extended frame ( + 18 cm)





COMPETITIVENESS:

